



Auto Grease White

A high quality calcium based grease, specially formulated to provide visible lubrication.



Features

- Calcium based
- 360° valve
- Silicone free
- Superior adhesion
- Viscostatic
- No harmful solvents
- Bright white in colour

Benefits

- Impervious to water unlike lithium based competitors
- Sprays at any angle
- Bodyshop safe
- Will not run or slump
- Retains properties over wide temp range
- Safe on virtually all components
- Visible to customers

Part N°: 84593 (AGW) - 500ml aerosol

Applications

Auto Grease White is most commonly used during vehicle servicing, for the lubrication of door hinges and check straps. It is also widely used for other areas where a heavier lubricant is required than KD400, such as seat runners, brake and clutch pedals, bonnet catches and hinges, choke and throttle linkages, sun roof runners, suspension bushes, leaf springs and window regulators.

Due to its thick consistency, AGW is not suitable for lubricating key barrels and fuel filler caps.

Being calcium based, AGW will not swell nylon, unlike lithium, which means that it can be safely used on areas like sun roof runners and runners for curtain side trucks.

Instructions

- Shake well before use.
- Apply as required, can sprays at any angle.



Technical Information

Part N°:	84593	Density @ 20 °C	0.8g/l
Description:	Auto Grease White, 500ml	Dropping Point °C;	>250 (DIN / ISO 2176)
Shelf Life:	30 months	Cone Penetration:	300-320 (DIN / ISO 2137) (0.1mm)
Selling Unit:	EA	NLGI Class:	1-2 (DIN 51818)
VOC:	530 g/L	Corrosion protection:	0-0 (DIN 51802)
Stock Code:	AGW	(Emcor Test):	+ 3% NaCl 2-2
Customs Tariff		Copper Corrosion:	1-100 (DIN 51811)
Code:	3403 99 10	Loading 4 ball test:	2600N (DIN 51350)
SDS:	Yes		
Temp range:	Range -20°C --+160°C		
Application temp:	10 – 35 °C		
Base:	Calcium complex soap, tackifier/corrosion inhibitors		
Solvents:	Aliphatic hydrocarbons		
Consistency:	Thick white grease,		



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 7/3/2017