

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **SILICONE GREASE**

Article number: 34920

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS09

Signal word *Danger*

Hazard-determining components of labelling:

pentane

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 1)

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing mist/vapours/spray.
 P280 Wear protective gloves / eye protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

vPvB:

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 68476-85-7 EINECS: 270-704-2	Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). Flam. Gas 1A, H220; Press. Gas (Comp.), H280	50-75%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	pentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	10-25%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes isoalkanes, cyclic Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-10%
CAS: 540-97-6 EINECS: 208-762-8 Reg.nr.: 01-2119517435-42	Dodecamethylcyclohexasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	<1%
CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	<1%
CAS: 556-67-2 EINECS: 209-136-7 Reg.nr.: 01-2119529238-36	octamethylcyclotetrasiloxane Flam. Liq. 3, H226; Repr. 2, H361f; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=10) PBT; vPvB	<1%

SVHC

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

Additional information

Note K is applicable for the product on one or more of its components. Classification in accordance with Annexe 1 for the reported danger properties. Contains < 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

Note P is applicable for the product on one or more of its components. Benzene concentration is <0.1% (w/w%)

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: **SILICONE GREASE**

(Contd. of page 2)

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** Rinse out mouth.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained breathing apparatus.
- **Additional information**
Cool endangered containers with water spray jet.
Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources
Ensure adequate ventilation
Particular danger of slipping on leaked / spilled product.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable containers.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on flames or red-hot objects.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
Store in cool location.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 3)

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Protect from heat and direct sunlight.

Store container in a well ventilated position.

5-35°C

· **Storage class 2 B**· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

· **Components with limit values that require monitoring at the workplace:****68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).**

WEL	Short-term value: 2180 mg/m ³ , 1250 ppm
	Long-term value: 1750 mg/m ³ , 1000 ppm
	Carc (if LPG contains > 0.1% of buta-1.3-diene)

109-66-0 pentaneWEL Long-term value: 1800 mg/m³, 600 ppm· **Regulatory information** WEL: EH40/2020· **DNELs****109-66-0 pentane**

Dermal Long term systemic effect 432 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 3,000 mg/m³ (Worker)**Hydrocarbons, C7, n-alkanes isoalkanes, cyclic**

Oral Long term systemic effect 149 mg/kg bw/day (Consumer)

Dermal Long term systemic effect 149 mg/kg/day (Consumer)

300 mg/kg/day (Worker)

Inhalative Long term systemic effect 447 mg/m³ (Consumer)2,085 mg/m³ (Worker)**7631-86-9 Silicon dioxide, chemically prepared**Inhalative Long term systemic effect 4 mg/m³ (Worker)**540-97-6 Dodecamethylcyclohexasiloxane**Inhalative Long term systemic effect 11 mg/m³ (Worker)Acute local effect 6.1 mg/m³ (Worker)Long term local effect 1.22 mg/m³ (Worker)**541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane**Inhalative Long term systemic effect 97.3 mg/m³ (Worker)Acute local effect 24.2 mg/m³ (Worker)Long term local effect 24.2 mg/m³ (Worker)Acute systemic effect 97.3 mg/m³ (Worker)**556-67-2 octamethylcyclotetrasiloxane**

Dermal Long term systemic effect 73 (Worker)

Inhalative Long term systemic effect 73 mg/m³ (Worker)Long term local effect 73 mg/m³ (Worker)· **PNECs****109-66-0 pentane**

PNEC 0.23 mg/l (Aqua (freshwater))

1.2 mg/kg (Freshwater sediment)

3.6 mg/l (Sewage treatment plant)

0.55 mg/kg (Soil)

540-97-6 Dodecamethylcyclohexasiloxane

PNEC 2.286 mg/kg (Freshwater sediment)

0.282 mg/kg (Marine water sediment)

>1 mg/l (Sewage treatment plant)

3.336 mg/kg (Soil)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 4)

541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclotetrasiloxane

PNEC >0.0012 mg/l (Aqua (freshwater))
>0.00012 mg/l (Aqua (marine water))
2.4 mg/kg (Freshwater sediment)
0.24 mg/kg (Marine water sediment)
>10 mg/l (Sewage treatment plant)
1.1 mg/kg (Soil)

556-67-2 octamethylcyclotetrasiloxane

PNEC 0.0015 mg/l (Aqua (freshwater))
3 mg/kg (Freshwater sediment)
0.3 mg/kg (Marine water sediment)
10 mg/l (Sewage treatment plant)
0.54 mg/kg (Soil)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
Avoid close or long term contact with the skin.
Wash hands during breaks and at the end of the work.
- **Breathing equipment:**
Only during spraying without adequate removal by suction.
Filter A1 (EN 14387)
- **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Wear suitable gloves tested to EN 374
NBR (0.35 mm)
Neoprene gloves

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Value for the permeation: Level 5 > 240 minutes

· Eye/face protection



Safety glasses (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Aerosol
· Colour:	Transparent
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 5)

· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	0.9 Vol % (Heptane)
· Upper:	10.9 Vol % (LPG)
· Flash point:	Not applicable, as aerosol
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible / difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 25 °C	0.75 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	540 g/l VOC
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 6)

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**· **Acute toxicity** Based on available data, the classification criteria are not met.· **LD/LC50 values that are relevant for classification:****109-66-0 pentane**

Oral	LD50	2,001 mg/kg (Rat)
Dermal	LD50	2,001 mg/kg (Rat)

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

Inhalative	LC50 (4 hr)	>23 mg/l (Rat)
	IC50	<10 (Algae)

7631-86-9 Silicon dioxide, chemically prepared

Oral	LD50	10,000 mg/kg (Rat)
------	------	--------------------

556-67-2 octamethylcyclotetrasiloxane

Oral	LD50	4,800 mg/kg (Rat) (OCSE 401)
Dermal	LD50	>2,400 mg/kg (Rat) (OECD TG 402)
Inhalative	LC50 (4 hr)	36 mg/l (Rat) (OECD TG 403)

· **STOT-single exposure** May cause drowsiness or dizziness.**11.2 Information on other hazards**· **Endocrine disrupting properties**

540-97-6	Dodecamethylcyclohexasiloxane	List II
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III

SECTION 12: Ecological information**12.1 Toxicity**· **Aquatic toxicity:****68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).**

EC50 (96 hr)	12.32 mg/l (Algae) ((Q)SAR calculation method)
LC50 (48 hr)	69.43 mg/l (Daphnia magna) ((Q)SAR calculation method)
LC50 (96 hr)	49.47 mg/l (Fish) ((Q)SAR calculation method)

109-66-0 pentane

EC50	10.7 mg/l (Pseudokirchneriella subcapitata) (72 hours)
EC50 (48 hr)	2.7 mg/l (Daphnia magna)
LC50 (96 hr)	4.26 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	7.51 mg/l (Pseudokirchneriella subcapitata)

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

EC50 (48 hr)	3 mg/l (Daphnia magna)
LC50 (96 hr)	<10 mg/l (Fish)
	>13.4 mg/l (Oncorhynchus mykiss)
NOEC	1.53 mg/l (Oncorhynchus mykiss) (28 days)
NOEC (21 days)	1 mg/l (Daphnia magna)

556-67-2 octamethylcyclotetrasiloxane

LC50	10 ug/l / (14 days) (Fish)
NOEC	0.0044 mg/l / (4 days) (Algae)
	0.0044 mg/l / (14 days) (Fish)

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 7)

12.5 Results of PBT and vPvB assessment**PBT:**

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

vPvB:

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:**General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS, MARINE POLLUTANT
IATA AEROSOLS, flammable

14.3 Transport hazard class(es)**ADR**

Class 2 5F Gases.

Label 2.1

IMDG, IATA

Class 2.1 Gases.

Label 2.1

14.4 Packing group

ADR, IMDG, IATA Void

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: SILICONE GREASE

(Contd. of page 8)

14.5 Environmental hazards:	
· Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	
· Kemler Number:	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according to IMO instruments	
	Not applicable.
Transport/Additional information:	
ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
I	0.9
NK	20.0

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

Substances of very high concern (SVHC) according to UK REACH

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 4 (replaces version 3)

Revision: 17.01.2023

Trade name: **SILICONE GREASE**

(Contd. of page 9)

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing data specification sheet: Environment protection department

Abbreviations and acronyms:

- RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- : Aerosols – Category 3
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Data compared to the previous version altered. *