

BlueSolar Polycrystalline Panels

www.victronenergy.com



BlueSolar Polycrystalline 175W

- Low voltage-temperature coefficient enhances high-temperature operation.
- Exceptional low-light performance and high sensitivity to light across the entire solar spectrum.
- 25-Year limited warranty on power output and performance.
- 5-Year limited warranty on materials and workmanship.
- Sealed, waterproof, multi-functional junction box gives high level of safety.
- High performance bypass diodes minimize the power drop caused by shade.
- Advanced EVA (Ethylene Vinyl Acetate) encapsulation system with triple-layer back sheet meets the most stringent safety requirements for high-voltage operation.
- A sturdy, anodized aluminium frame allows modules to be easily roof-mounted with a variety of standard mounting systems.
- Highest quality, high-transmission tempered glass provides enhanced stiffness and impact resistance.
- High power models with pre-wired quick-connect system with MC4 (PV-ST01) connectors.



MC4 connectors

Article Number	Description	Net weight	Electrical data under STC (1)				
			Nominal Power	Max-Power Voltage	Max-Power Current	Open-Circuit Voltage	Short-Circuit Current
			PMPP	VMPP	IMPP	Voc	Isc
		Kg	W	V	A	V	A
SPP040201200	Discontinued	1.9	20	18.4	1.09	21.96	1.18
SPP040301200	Discontinued	2.8	30	18.2	1.66	21.80	1.80
SPP040451200	Discontinued	3.1	45	19.1	2.36	22.90	2.55
SPP040601200	Discontinued	4	60	19.3	3.12	23.10	3.37
SPP040901200	Discontinued	6.1	90	19.5	4.61	23.44	4.98
SPP041151202	Discontinued	8	115	18.9	6.08	22.73	6.56
SPP041301200	130W-12V Poly 1200 x 668 x 30mm series 4a	9.1	130	18.5	7.02	22.71	7.39
SPP041751200	175W-12V Poly 1485 x 668 x 30mm series 4a	12	175	18.3	9.56	21.9	10.24
SPP042702000	Discontinued	18.4	270	31.7	8.52	38.04	9.21
SPP042802000	Discontinued	18.4	280	31.9	8.77	39.13	9.23
SPP043302402	330W-24V Poly 1980 x 1002 x 40mm series 4b	23	330	37.3	8.86	44.72	9.57

Module	SPP 040201200	SPP 040301200	SPP 040451200	SPP 040601200	SPP 040901200	SPP 041151202	SPP 041301200	SPP 041751200	SPP 042702000	SPP 042802000	SPP 043302402
Nominal Power (± 3% tolerance)	20W	30W	45W	60W	90W	115W	130W	175W	270W	280W	330W
Cell type	Polycrystalline										
Number of cells in series	36								60		72
Maximum system voltage (V)	1000V										
Temperature coefficient of PMPP (%)	-0.45/°C	-0.45/°C	-0.45/°C	-0.45/°C	-0.45/°C	-0.45/°C	-0.45/°C	-0.45/°C	-0.47/°C	-0.40/°C	-0.45/°C
Temperature coefficient of Voc (%)	-0.35/°C	-0.35/°C	-0.35/°C	-0.35/°C	-0.35/°C	-0.35/°C	-0.35/°C	-0.35/°C	-0.34/°C	-0.30/°C	-0.35/°C
Temperature coefficient of Isc (%)	+0.04/°C	+0.04/°C	+0.04/°C	+0.04/°C	+0.04/°C	+0.04/°C	+0.04/°C	+0.04/°C	+0.045/°C	+0.06/°C	+0.04/°C
Temperature Range	-40°C to +85°C										
Surface Maximum Load Capacity	200 kg/m²										
Allowable Hail Load	23 m/s, 7.53 g										
Junction Box Type	PV-LH0805	PV-LH0806		PV-LH0801		PV-LH0808			PV-JB002		
Length of Cable / connector	No cable				900 mm / MC4						
Output tolerance	+/-3%										
Frame	Aluminium										
Product warranty	5 years										
Warranty on electrical performance	10 years 90% + 25 years 80% of power output										
Smallest packaging unit	1 panel										
Quantity per pallet	380	240	200	140	72	72	72	48	42	42	37

1) STC (Standard Test Conditions): 1000 W/m², 25°C, AM (Air Mass) 1.5